



EMBLEM MULTI GRADE SAE 10W30

EMBLEM Motor Oil SAE 10W-30 is a superior quality, multi-viscosity oil with a wide range that permits easy starting at low temperatures and sufficient body to protect at normal operating temperature. This oil is formulated with special dispersant detergent additives to keep suspended harmful by-products of combustion. In addition, other additives have been combined to protect against wear, rust corrosion, and oxidation. **EMBLEM** Multi-Grade SAE 10W-30 is recommended for use in all passenger cars and light duty trucks. It is also recommended as a superior lubricant for other types of four-cycle gasoline powered equipment. In addition, **EMBLEM** Multi-Grade SAE 10W-30 is an excellent choice for diesel-powered passenger cars and light duty trucks where a SAE 10W-30 grade is recommended.

Typical Properties

Viscosity, SUS @ 210 °F	63
Viscosity, cSt @ 100 °C	10.7
Viscosity, SUS @ 100 °F	375
Viscosity, cSt @ 40 °C	69
Viscosity, CCS cP @ - 25°C	6000
Viscosity Index	145
Gravity °API	29.8
Flash Point COC °F	410
Fire Point COC °F	440
Pour Point °F	- 33
Color	3.0
Sulfated Ash, % wt.	.85

EMBLEM Multi-Grade SAE 10W-30 meets or exceeds the performance requirements of the following:

API Service: SM ECII

ILSAC GF-4,GF-3,GF-2,GF1