



## EMBLEM SUPREME SAE 15W40

**EMBLEM** Supreme SAE 15W-40 is a new exceptionally versatile premium-quality multi-grade universal extended drain crankcase oil for diesel and gasoline engines. Manufactured from selected premium, high-viscosity-index base oils and formulated to exceed the latest requirements of heavy-duty diesel engines, including the rigorous Mack trucks EOM specification. In addition, **EMBLEM** Supreme SAE 15W40 meets the latest gasoline engine requirements under all operating conditions where the equipment owner wishes the additional performance benefits of multi-grade oils.

### Typical Properties

Viscosity, SUS @ 210 °F	79.9
Viscosity, SUS @ 100 °F	538
Viscosity, CCS @ - 20 °C	5900
Viscosity Index	140
Gravity °API	29.3
Flash Point COC °F	420
Pour Point °F	- 22
Pour Point °C	- 33
Color ASTM D1500	3.5
TBN (ASTM D 2896)	9.4
Sulfated Ash, % wt.	1.2

Emblem Multi-Grade SAE 15W-40 meets or exceeds the performance requirements of the following:

API Service:CI-4 CH-4 CF SL CD-II ,CE /SL  
 Mack EO-M Plus, EO-L EO-J, EO-K, EO-K2  
 Cummins CES 20078 approved  
 Allis Chalmers  
 GMC 6049-M

Allison Type C-3/C-4 transmission fluid  
 Volvo VDS/VDS-2 and ACEA E2/B3/A3  
 CAT ECF-1

Diesel - CAT TO-2  
 International Harvester  
 John Deere  
 Detroit Diesel Allison  
 Ford M2C171-D

Military - MIL-L-2104D, MIL-L-46152B, (Former) MIL-L-2104B

