



EMBLEM EXTRALUBE HD MOTOR OILS

EMBLEM Extralube HD Motor Oils are premium quality, heavy duty motor oils available in five SAE viscosities: SAE10W, SAE 20W20, SAE30, SAE40 and SAE50. These oils combine top quality base stocks with the finest additives available to assure exceptional resistance to formation of high or low temperature engine varnish and sludge. They also feature long time engine protection against wear, corrosion, rust, foam and combustion chamber deposits. In addition they help keep PVC (positive crankcase ventilation) systems clean and working properly.

Typical Properties

SAE GRADE	10W	20W20	30	40	50
Viscosity, SUS @ 210 °F	46	55	66	78	98
Viscosity, SUS @ 100 °F	185	285	465	730	1100
Viscosity, CCS @ - 18 °C	12000	48000	---	---	---
Viscosity Index	100	100	100	100	100
Gravity °API	29.5	28.5	28.0	27.0	26.5
Flash Point COC °F	410	425	435	440	450
Pour Point °F	- 20	- 10	0	10	15
Color	3	5	5	6	7

EMBLEM Extralube HD Motor Oils meet or exceeds the performance requirements of the following:

API Service: SF-SG/CC-CD

GMC 6049-M
Chrysler MS 6395

Ford, ESE-M2C153-C
Military Specification MIL-L-46152B