



UNIPLEX NO. 2

Uniplex No. 2 is a Lithium Complex Grease that has an extreme range of applications such as off-road equipment, trucks, automobiles, and industrial equipment. It is recommended for all wheel bearings, universal joints, chassis, ball and roller bearings, throw-out bearings, and electric motors.

Uniplex No. 2 offers many advantages such as:

Excellent metal adhesion

Water resistant

Rust protection

Long Life

Extreme pressure protection

Resists break-down under load conditions

Compatible with most other greases

Affords low/high temperature protection

Typical Properties

N.L.G.I. GRADE	2			
Dropping Point, D-2265 °F	570			
Water Washout, D-1264				
% Loss @ 100 °F	2			
% Loss @ 175 °F	5			
Low Temp. Torque				
ASTM G-3-11	1	2	3	
Torque @ - 40 °C., N.M.	START	14.0	11.0	10.2
	1 MINUTE	8.6	4.5	4.9
	3 Minutes	7.0	4.3	4.6
	5 Minutes	6.1	4.1	4.4
	10 Minutes	5.0	3.6	4.0
Separated Mineral Oil:				
Viscosity, SUS @ 100 °F	590			
Viscosity, SUS @ 210 °F	69			

Viscosity Index	100
Flash Point, COC °F	465
Fire Point, COC °F	500
Pour Point, °F	- 25
Thickener, Type	Complex Lithium 12-OH
Thickener, %	6-9
Color & Texture	Medium Amber - Smooth - Buttery