



EMBLEM UTH 303 UNIVERSAL TRACTOR HYDRAULIC

EMBLEM UTH (Universal Tractor Hydraulic) was developed for the increased demands for a single multi-functional hydraulic oil used in transmissions, brakes and steering of the new generation of tractors and like equipment. This product serves as a lubricant, coolant and power transfer fluid and provides shear stability, foam control, water tolerance, "grabbing control" and high film strength features. UTH is recommended for use in John Deere, International Harvester, Ford, Allis Chalmers, J.I. Case and Massey Ferguson equipment.

Typical Properties

Viscosity, SUS @ 210 °F	50-55
Viscosity, SUS @ 100 °F	App. 280
Viscosity Index	115
Gravity °API	28-30
Flash Point COC °F	400
Pour Point °F	- 30
Color	3.0
Aniline Point (TYP)	208

For use where the following specification fluids are prescribed:

Allison	C-3, C-4
Allis Chalmers	Power Fluid 821
J.I. Case	JIC-185; JIC-;145;MS105;MS1204;MS1206; MS1207; MS1210
CAT	TO-2
John Deere	J-20A,B,C & D; J-14C; J-21A
Deutz-Allis	PF821XL
Ford	M2C86; M2C134;M2C48C
International Harvester	Hy-Tran
Kubota	B6 (UDT)
Massey Ferguson	M-1110; M-1127A; M-1129A; M-1135;M1127B,M1139;M1141

Versatile	23M or 24M
Vickers	35VQ25
White Farm	UHTF Type 55;Q1826